

delivering
quality service

WASHER FEATURES

- Unique patented Honeycomb drum
- Easy to use
- Short programmes
- Large drum volume
- Practical accessories
- Simple programme selection
- Time-saving cloth impregnation
- Barrier-free draining

Miele Little Giant PW5064

the new washing machine for contract cleaners



WASH

Laundryserv

Unit 4 Alpha Industrial Park, Bevan Way,
Smethwick, B66 1BZ

telephone

0800 7311 399

fax

0121 565 1070

enquiries@phs.co.uk

www.laundryserv.co.uk

Laundryserv

TECHNICAL FEATURES

Whether it's a school, office or production plant, mop heads and cleaning cloths need to be cleaned thoroughly, often several times a day. In hygienically sensitive areas such as hospitals and care centres, it is also vital that these are thoroughly disinfected.

Unique Honeycomb drum has small, smooth holes in the drum walls to ensure textiles are subject to minimum wear & tear.

Short effective programmes ensure fast mop head turnaround times and high throughput.

Intelligent technology reinforced shock absorbers, excellent quiet running properties & robust drum bearing cope with the rough & tumble of commercial applications

Time-saving cloth impregnation after cleaning ensure that cloths leave the washer disinfected and hygienically clean.

Barrier-free drainage prevents drains from clogging. Equipped with a newly developed drain valve with increased cross-sectional diameter prevents clogging and deposits even in the face of coarse soiling.

Cost saving, highly efficient technology. Mop heads last longer thanks to patented honeycomb drum. Save on detergents due to intelligent cloth impregnation. Hot water fill application for reduced electricity consumption. Long machine life cycle.

PW 5064

Capacity (kg)	6.5
Height (mm)	850
Width (mm)	595
Depth (mm)	725
Net weight (kg)	107
Spin speed (rpm)	1399
Water (hot & cold)	Min 1 bar, max 10 bar
Water inlet	½ inch
Drain (gravity)	Hot and cold water connection
Electrics	13amp / 30amp
Total rated load	2.5 13amp / 5.5 30amp
Floor requirements	solid, level
Cycle Time (min)	
Sluice	n/a
Standard	43 mins (30amp)
Airgap Type	WRAS approved
Available options	
Coin Operated	n/a
Stackable	Y
Plinth	Y



WASH