

Miele dishwashers

quality, commercial equipment

Dishwasher Features

- Unique wash systems
- Variety of basket configurations
- Simple controls
- Pass through models
- Front loading models
- Tank fed systems
- Freshwater systems
- WRAS approved
- Thermal disinfection cycles



Miele
PROFESSIONAL



wash

Dishwasher Features

Laundryserv offer the complete range of Miele pass through and front loading dishwashers to suit every environment

unique wash system consists of three upper and lower rotating spray arms

WRAS approved ensures it complies with the current water regulations for connection direct to the mains water supply.

electric controls allows for versatile programming of cleaning programmes

variety of basket configurations ensure the dishwasher is tailored for your needs

simple controls make all models easy to use

pass through models offer high throughput for very busy kitchens

front loading models are ideal for fitting under counters

tank fed systems ensure the dishwasher is always ready to run, as the temperature of the wash water is held at 65 °C

freshwater systems use fresh water for each stage of the programme ensuring you can clean mixed loads

thermal disinfection programme on G7859TD is fully compliant with NHS guidelines for cycle temperature and length

| Miele PROFESSIONAL | G8050 | G7859 TD | G7855 | G7856 | G8066 | G8072 |
|------------------------------------|----------------------------------|------------------------------|----------------------------|------------------------------|--|--|
| Loading | Front | Front | Front | Front | Front | Pass through |
| Water system | Fresh | Fresh | Fresh | Fresh | Tank | Tank |
| Height (mm) | 850 | 850 | 850 | 850 | 820 | 1940 |
| Width (mm) | 600 | 600 | 600 | 600 | 598 | 635 |
| Depth (mm) | 600 | 600 | 600 | 600 | 600 | 750 |
| Net weight (kg) | 63.5 | 76 | 77 | 70 | 77 | 118 |
| Water connection (Hot & Cold) | 1x cold or hot water (max 60 °C) | 1x cold & 1x hot (max 70 °C) | 1x cold or hot (max 70 °C) | 1x cold & 1x hot (max 70 °C) | 1x cold or hot water (max 70 °C) | 1x cold or hot water (max 70 °C) |
| Drain | Pump | Pump | Pump | Pump | Pump | Pump |
| Electrics | 13amp | 240V 30amp / 3 phase | 240V 30amp | 240V 30amp / 3 phase | 3 phase or 240V 30 amp 6kW hot fill only | 3 phase or 240V 30 amp 6kW hot fill only |
| Number of Programmes | 6 | 4 std & 3 disinfect | 7 | 8 | 3 and 1 self clean | 3 |
| Shortest programme | 15 min (glassware) | 18 min | 11 min | 7 min | 1.5 min | 1 min |
| WRAS APPROVED PRODUCT | Y | Y | Y | Y | Y | Y |
| No. baskets | 2 | 2 | 2 | 2 | 1 | 1 |

Laundryserv are committed to providing a complete quality service including:

- A 24 / 7 staffed contact line
- A choice of Service Level Agreements, including an 8 hour response option
- 95% First time fix rates
- Preventative maintenance visits
- Nationwide team of fully qualified, trained engineers
- Choice of full service rental or purchase and callout packages

