

## Laundryserv

Unit 4 Alpha Industrial Park, Bevan Way  
Smethwick. B66 1BZ

telephone  
0800 7311 399

fax  
0121 565 1070

enquiries@phs.co.uk  
www.laundryserv.co.uk



### INDUSTRIAL CYLINDER HEATED DRYING IRONERS with LENGTH FOLDING and AUTOMATIC FEEDING

**easy to operate**, programmable ironer with length folding with single person operation.

**finger guard & emergency stop** for added operator safety.

**chrome plated roller** for even heat dispersion and premium finish.

**self diagnosis** helps to detect and diagnose any faults that may occur, helping to simplify any maintenance.

**large surface contact** of over 300° with the fabric and the roller helps the finish and throughput.

**high ironing pressure** ensures a premium finish.

**large built in laundry box** at the front of the machine captures ironed linen.

**displays speed & temperature** makes it easy to ensure set up is correct for the fabric type.

	IFF50 (200)	IFF50 (250)	IFF50 (320)
Capacity* (kg / hr)	50	70	90
Height (mm)	1760	1760	1760
Width (mm)	2850	3450	4050
Depth (mm)	1320	1320	1320
Net weight (kg)	1720	2460	2770
Roller Length (m)	2	2.5	3.2
Roller Diameter (mm)	500	500	500
Roller Speed (m / min)		1.5 – 8	
Electricity		3 phase only	
Electric Heating (kW)	37	70	n/a
Gas (btu)	135,000	200,000	250,000
Exhaust	6"	2 x 6"	2 x 6"
Floor requirements		Solid, level	
Available options		Gas / Electric / Steam heating Foot Pedal Crossfolder & stacker	



# IRON

drying ironers

\*The capacities are indications only, and will vary dependent on the residual moisture, fabric type, ironing temperature, pressure of the ironing bed, condition of the surface and the skill of the operator

All images and specifications are for reference only.  
Laundryserv reserves the right to change any of these without notice

issue 02 July 2009

Laundry*serv*

delivering  
quality service

# Drying ironers

professional ironing solutions

IRON

# Ironers range

professional ironing solutions

## INDUSTRIAL CYLINDER HEATED DRYING IRONER FEATURES

**easy to operate**, programmable ironer with adjustable temperature and roller speed makes it ideal for all fabric types.

**finger guard & emergency stop** for added operator safety.

**chrome plated roller** for even heat dispersion and premium finish.

**self diagnosis** helps to detect and diagnose any faults that may occur, helping to simplify any maintenance.

**large surface contact** of over 300° with the fabric and the roller helps the finish and throughput.

**high ironing pressure** ensures a premium finish.

**large built in laundry box** at the front of the machine captures ironed linen.

**speed & temperature display** makes it easy to ensure set up is correct for the fabric type.

	I-35 (140)	I-35 (160)	I-35 (200)	I-50 (160)	I-50 (200)	I-50 (250)	I-50 (320)
--	---------------	---------------	---------------	---------------	---------------	---------------	---------------

Capacity* (kg / hr)	27	32	40	45	60	80	100
Height (mm)	1180	1180	1180	1232	1232	1232	1232
Width (mm)	2150	2350	2750	2350	2750	3350	3950
Depth (mm)	875	875	875	992	992	992	992
Net weight (kg)	580	670	700	920	1150	1290	1590
Roller Length (m)	1.4	1.6	2	1.6	2	2.5	3.2
Roller Diameter (mm)	350	350	350	500	500	500	500
Roller Speed(m / min)				1.5 – 8			
Electricity				3 phase & neutral			
Electrics (kW)	17	25	29	38	n/a	n/a	n/a
Gas (btu)	100,000	220,000	220,000	120,000	135,000	200,000	250,000
Exhaust	6"	6"	6"	6"	6"	6"	6" x 2
Floor requirements				Solid, level			
Available options	{ Gas / Electric }			{ Gas / Electric / Steam }			
				Foot pedal			



**INDUSTRIAL CYLINDER  
HEATED DRYING IRONERS  
with LENGTH FOLDING**

**easy to operate**, programmable ironer with length folding with single person operation.

**finger guard & emergency stop** for added operator safety.

**chrome plated roller** for even heat dispersion and premium finish.

**self diagnosis** helps to detect and diagnose any faults that may occur, helping to simplify any maintenance.

**large surface contact** of over 300° with the fabric and the roller helps the finish and throughput.

**high ironing pressure** ensures a premium finish.

**large built in laundry box** at the front of the machine captures ironed linen.

**speed & temperature display** makes it easy to ensure set up is correct for the fabric type.

	<b>IF50 (200)</b>	<b>IF50 (250)</b>	<b>IF50 (320)</b>
Capacity* (kg / hr)	50	70	90
Height (mm)	1568	1568	1568
Width (mm)	2750	3350	3950
Depth (mm)	1185	1185	1185
Net weight (kg)	1290	1440	1680
Roller Length (m)	2	2.5	3.2
Roller Diameter (mm)	500	500	500
Roller Speed(m / min)		1.5 – 8	
Electricity		3 phase only	
Electrics (kW)	50	70	85
Gas (btu)	135,000	200,000	250,000
Exhaust	6"	2 x 6"	2 x 6"
Floor requirements		Solid, level	
Available options		Gas / Electric / Steam heating Foot Pedal	

